

# The pdfcrypt package

Heiko Oberdiek  
<heiko.oberdiek at gmail.com>

2007/04/26 v1.0

## Abstract

This package supports the setting of pdf encryption options for V $\text{\TeX}$  and some older versions of pdf $\text{\TeX}$ .

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	Alternatives	2
1.2	Usage	2
1.2.1	Special characters	3
1.2.2	<code>\nopdfcrypt</code>	3
1.2.3	Configuration file	3
1.2.4	Support for plain $\text{\TeX}$	3
1.3	Hints for pdf $\text{\TeX}$	3
<b>2</b>	<b>Implementation</b>	<b>4</b>
2.1	Help macros for plain $\text{\TeX}$	4
2.2	Package Identification and checks	5
2.3	Driver detection	5
2.4	Load package <code>keyval</code>	6
2.5	Define options	7
2.6	support of configuration file	11
2.7	Package options	11
<b>3</b>	<b>Installation</b>	<b>12</b>
3.1	Download	12
3.2	Bundle installation	12
3.3	Package installation	12
3.4	Refresh file name databases	12
3.5	Some details for the interested	13
<b>4</b>	<b>History</b>	<b>13</b>
[2001/04/02 v0.1]		13
[2001/07/19 v0.2]		13
[2001/07/19 v0.3]		13
[2001/07/19 v0.4]		13
[2001/08/05 v0.5]		13
[2001/08/09 v0.6]		14
[2001/10/28 v0.7]		14
[2006/02/20 v0.8]		14
[2007/04/11 v0.9]		14
[2007/04/26 v1.0]		14
<b>5</b>	<b>Index</b>	<b>14</b>

# 1 Documentation

This package allows the setting of pdf encryption options for

- V<sub>T</sub>E<sub>X</sub>, since version 7.35, <http://www.micropress-inc.com/>.
- pdf<sub>T</sub>E<sub>X</sub>, patched by Ricardo Sanchez Carmenes<sup>1</sup>.  
Some supported versions are:

```
pdfTEX-1.00a,  
pdfTEX-0.14h-pdfcrypt-20010310,  
pdfcrypt-20010331
```

**Note:** Since pdf<sub>T</sub>E<sub>X</sub>-1.10a (2003-01-16) encryption support was dropped! Thus the package is now obsolete for recent pdf<sub>T</sub>E<sub>X</sub> versions.

## 1.1 Alternatives

There are free alternatives, programs that can be used for postprocessing the pdf file:

- pdftk  
<http://www.accesspdf.com/pdftk/>
- Multivalent  
<http://multivalent.sourceforge.net/>
- PDFBox  
<http://www.pdfbox.org/>
- PDFTrans  
<http://maddingue.free.fr/software/pdftrans.html>
- ...

## 1.2 Usage

The options can be set as package options or with the command `\pdfcryptsetup`:

```
owner=<owner password>  
user=<user password>  
print, copy, edit, annotate=true, false  
all, none  
debug
```

The encryption is set at `\begin{document}` by default, but this can be forced for an earlier time using the option `set`. Example:

```
\usepackage [owner=Donald,user=Knuth,print=false]{pdfcrypt}  
...  
\begin{document}
```

or

```
\usepackage{pdfcrypt}  
\pdfcryptsetup{owner=Donald,user=Knut}  
\pdfcryptsetup{print=false,set}  
...  
\begin{document}
```

---

<sup>1</sup>Ricardo Sanchez Carmenes's email address: [carmenes@bioquimica.uniovi.es](mailto:carmenes@bioquimica.uniovi.es)

### 1.2.1 Special characters

The characters ‘{’, ‘}’, and ‘\’ have to be escaped with ‘\’. Then the string should not be specified as package option but with the macro `\pdfcryptsetup`, eg:

```
\pdfcryptsetup{user={\{\Hello\}},print=false}
```

The password here is “`{\Hello}`”. Active characters can be used and are not expanded. Macros except for `\{`, `\}`, and `\\` should not be used and are not expanded.

### 1.2.2 \nopdfcrypt

Often the whole process of pdf generation includes several  $\TeX$  compilations and perhaps other postprocessing steps. Therefore a feature would be useful to disable the encryption stuff in order to speed up the first compilations. Therefore package `pdfcrypt` will look for the macro `\nopdfcrypt`. If it has the meaning of the letter ‘Y’, the package will be disabled. Example:

```
pdflatex '\let\nopdfcrypt=Y\input myfile'  
thumbpdf myfile  
pdfelatex myfile
```

### 1.2.3 Configuration file

If the file `pdfcrypt.cfg` exists it is loaded and can be used for common settings.

### 1.2.4 Support for plain $\TeX$

The package can also be used with plain  $\TeX$ . It defines the missing  $\LaTeX$  macros and loads package `keyval`. The configuration file is not supported and automatically loaded.

## 1.3 Hints for pdf $\TeX$

This section is out of date, because the encryption support was removed from pdf $\TeX$ . Therefore this hints are of historical interest only.

- \* There are packages such as `thumbpdf` that ship out some stuff (`\immediate\pdfobj{...}`). In these cases `\pdfcrypt` will be ignored without warning or error message. Therefore the package `pdfcrypt` should be loaded before and option "set" should be used in order to force the call of `\pdfcrypt`, for example:

```
\usepackage{pdfcrypt}  
\pdfcryptsetup{..., set}  
...  
\usepackage{thumbpdf}
```

- \* Compiling pdf $\TeX$  (eg. version 1.00a-pretest-20010804):  
pdf $\TeX$  versions are available at  
`ftp://ftp.cstug.cz/pub/tex/local/cstug/thanh/pdftex/snapshots/`  
Unpack the latest .tgz file:  
`> tar xzf pdftex-20010804.tgz`  
Enable encryption support:  
`src> cd src/tekk/web2c/pdftexdir`  
`src/tekk/web2c/pdftexdir> ln -fs pdfcrypt-full.c pdfcrypt.c`  
Compile:  
`src/tekk/web2c/pdftexdir> cd ../../..`  
`src> ./configure`  
`src> cd tekk/web2c`  
`src/tekk/web2c> make pdftexbin`  
At last install the binary and pool files.

## 2 Implementation

```
1 (*package)
```

### 2.1 Help macros for plain T<sub>E</sub>X

```
2 \expandafter\edef\csname pc@endinput\endcsname{%
3   \catcode'\noexpand\@=\the\catcode'\@\relax
4   \noexpand\endinput
5 }
6 \catcode'\@=11 %
7
8 \expandafter\ifx\csname @firstoftwo\endcsname\relax
9   \long\def\@firstoftwo#1#2{#1}%
10 \fi
11
12 \expandafter\ifx\csname @secondoftwo\endcsname\relax
13   \long\def\@secondoftwo#1#2{#2}%
14 \fi
15
16 \expandafter\ifx\csname @ifundefined\endcsname\relax
17   \def\@ifundefined#1{%
18     \expandafter\ifx\csname #1\endcsname\relax
19       \expandafter\@firstoftwo
20     \else
21       \expandafter\@secondoftwo
22     \fi
23   }%
24 \fi
25
26 \@ifundefined{@ifnextchar}{%
27   \long\def\@ifnextchar#1#2#3{%
28     \let\reserved@d=#1%
29     \def\reserved@a{#2}%
30     \def\reserved@b{#3}%
31     \futurelet\@let@token\@ifnch
32   }%
33   \def\@ifnch{%
34     \ifx\@let@token\@sptoken
35       \let\reserved@c\@xifnch
36     \else
37       \ifx\@let@token\reserved@d
38         \let\reserved@c\reserved@a
39       \else
40         \let\reserved@c\reserved@b
41       \fi
42     \fi
43     \reserved@c
44   }%
45   \begingroup
46     \def\:\{\global\let\@sptoken= }%
47     \: %
48     \def\:\{\@xifnch}%
49     \expandafter\gdef\:\ {\futurelet\@let@token\@ifnch}%
50   \endgroup
51 }{}
52
53 \@ifundefined{ProvidesPackage}{%
54   \def\ProvidesPackage#1{%
55     \@ifnextchar[{\pc@ProvidesPackage{#1}}%
56       {\pc@ProvidesPackage{#1}[]}%
57   }%
58   \def\pc@ProvidesPackage#1[#2]{%
```

```

59   \immediate\write-1{Package: #1 #2}%
60 }%
61 }{}
62
63 \begingroup\expandafter\expandafter\expandafter\endgroup
64 \expandafter\ifx\csname RequirePackage\endcsname\relax
65   \input infwarerr.sty\relax
66 \else
67   \RequirePackage{infwarerr}%
68 \fi
69
70 \@ifundefined{@gobble}{%
71   \long\def@gobble#1{%
72 }{}
73
74 \@ifundefined{@empty}{%
75   \def@empty{}%
76 }{}

```

## 2.2 Package Identification and checks

```

77 \ProvidesPackage{pdfcrypt}%
78 [2007/04/26 v1.0 Setting pdf encryption (HO)]%
79 \@ifundefined{pdfcryptsetup}{%
80   \let\pdfcryptsetup@gobble
81 }{}
82 \@PackageWarningNoLine{pdfcrypt}{Package pdfcrypt is already loaded}%
83 \pc@endinput
84 }

```

Support for \nopdfcrypt.

```

85 \newif\ifpc@nopdfcrypt
86 \ifx Y\nopdfcrypt
87   \@PackageWarningNoLine{pdfcrypt}{%
88     Encryption disabled by \string\nopdfcrypt\space request%
89   }%
90   \global\pc@nopdfcrypttrue
91 \fi

```

## 2.3 Driver detection

```

92 \let\pc@driver@empty
93 \begingroup
94   % pdfTeX detection
95   \@ifundefined{pdfoutput}{%
96   }{%
97     \ifcase\pdfoutput
98     \else
99       \@ifundefined{pdfcrypt}{%
100         \@PackageError{pdfcrypt}{%
101           PDF encryption is not supported with this pdfTeX%
102         }{%
103           Encryption support was added in 0.14h (2001/03/10)\MessageBreak
104           and removed in 1.10a (2003/01/16).%
105         }%
106       \endgroup
107       \pc@endinput
108     }{}
109     \gdef\pc@driver{pdftex}%
110   }%
111   \fi
112 }%
113 % VTeX detection
114 \@ifundefined{OpMode}{%

```

```

115 }{%
116   \ifnum\OpMode=1 %
117     \ifnum\@ifundefined{VTeXversion}0\VTeXversion<735 %
118       \@PackageError{pdfcrypt}{%
119         PDF encryption is not supported with this VTeX%
120       }{%
121         You need VTeX 7.35 or higher.%
122       }%
123     \endgroup
124     \pc@endinput
125   \else
126     \gdef\pc@driver{vtex}%
127     \fi
128   \fi
129 }%
130 \endgroup

```

## 2.4 Load package keyval

```

131 \@ifundefined{@makeother}{%
132   \def\@makeother#1{\catcode'#1=12\relax}%
133 }{}
134
135 \@ifundefined{g@addto@macro}{%
136   \long\def#g@addto@macro#1#2{%
137     \begingroup
138     \toks@\expandafter{#1#2}%
139     \xdef#1{\the\toks@}%
140   \endgroup
141 }%
142 }{}
143
144 \@ifundefined{@namedef}{%
145   \def\@namedef#1{\expandafter\def\csname#1\endcsname}%
146 }{}
147
148 \@ifundefined{@nameuse}{%
149   \def\@nameuse#1{\csname #1\endcsname}%
150 }{}
151
152 \def\pc@KeyvalRestore{%
153   \let\pc@KeyvalRestore\undefined
154 }
155
156 \let\pcOrg@NeedsTeXFormat\NeedsTeXFormat
157 \@ifundefined{NeedsTeXFormat}{%
158   \def\NeedsTeXFormat#1{%
159     \g@addto@macro\pc@KeyvalRestore{%
160       \let\NeedsTeXFormat\pcOrg@NeedsTeXFormat
161     }%
162 }{}
163
164 \let\pcOrg@DeclareOption\DeclareOption
165 \@ifundefined{DeclareOption}{%
166   \def\DeclareOption#1#2#3{%
167     \g@addto@macro\pc@KeyvalRestore{%
168       \let\DeclareOption\pcOrg@DeclareOption
169     }%
170 }{}
171
172 \let\pcOrg@ExecuteOptions\ExecuteOptions
173 \@ifundefined{ExecuteOptions}{%
174   \def\ExecuteOptions#1{%

```

```

175 \g@addto@macro\pc@KeyvalRestore{%
176   \let\ExecuteOptions\pcOrg@ExecuteOptions
177 }%
178 }{}
179
180 \let\pcOrg@ProcessOptions\ProcessOptions
181 \@ifundefined{ProcessOptions}{%
182   \def\ProcessOptions{}%
183   \g@addto@macro\pc@KeyvalRestore{%
184     \let\ProcessOptions\pcOrg@ProcessOptions
185   }%
186 }{}%
187
188 \begingroup\expandafter\expandafter\expandafter\endgroup
189 \expandafter\ifx\csname RequirePackage\endcsname\relax
190   \input keyval.sty\relax
191 \else
192   \RequirePackage{keyval}%
193 \fi
194 \pc@KeyvalRestore

```

## 2.5 Define options

```

195 \@ifundefined{@dblarg}{%
196   \long\def@dblarg#1{\@ifnextchar[#{1}]{\@xdblarg{#1}}}%
197   \long\def@xdblarg#1#2{#1[#{2}]{#2}}%
198 }{}
199
200 \newif\ifpc@set
201 \newif\ifpc@print
202 \newif\ifpc@copy
203 \newif\ifpc@edit
204 \newif\ifpc@annotate
205 \newif\ifpc@debug
206 \let\pc@owner\@empty
207 \let\pc@user\@empty
208
209 % default: allow all
210 \pc@printtrue
211 \pc@copytrue
212 \pc@edittrue
213 \pc@annotatetrue
214
215 \edef\pc@temp{\catcode'\noexpand\="=\the\catcode'\'\relax}
216 \@makeother\
217 \def\pc@set{%
218   \@PackageInfo{pdfcrypt}{%
219     \ifpc@debug
220       \ifx\pc@owner\@empty
221         No owner password%
222       \else
223         Owner password: '\pc@owner'%
224       \fi
225       \MessageBreak
226       \ifx\pc@user\@empty
227         No user password%
228       \else
229         User password: '\pc@user'%
230       \fi
231       \MessageBreak
232       Flags: %
233       \ifpc@print   \else no\fi print, %
234       \ifpc@copy    \else no\fi copy, %

```

```

235     \ifpc@edit    \else no\fi edit, %
236     \ifpc@annotate\else no\fi annotate%
237     \MessageBreak
238     \fi
239     \ifpc@nopdfcrypt
240     Encryption is disabled by '\string\nopdfcrypt'%
241     \else
242     Encryption is set for '\pc@driver'%
243     \fi
244 }%
245 \ifpc@nopdfcrypt
246 \else
247   \@ifundefined{pc@set@\pc@driver}{%
248     \ifx\pc@driver\@empty
249       \@PackageError{pdfcrypt}{No driver for encryption %
250         support found}\@ehc
251     \else
252       \@PackageError{pdfcrypt}{Cannot set encryption for %
253         unknown driver '\pc@driver'}\@ehc
254     \fi
255   }-%
256   \@nameuse{pc@set@\pc@driver}%
257 }%
258 \fi
259 }
260 \def\pc@set@pdftex{%
261   \ifnum\pdftexversion<100 %
262     \pc@set@pdftexold
263   \else
264     \pc@set@pdftexnew
265   \fi
266 }
267 \def\pc@set@pdftexold{%
268   \pdfcrypt{%
269     owner "\pc@owner" %
270     user "\pc@user" %
271     \ifpc@print    \else no\fi print %
272     \ifpc@copy     \else no\fi copy %
273     \ifpc@edit     \else no\fi edit %
274     \ifpc@annotate\else no\fi annotate%
275   }%
276 }
277 \def\pc@set@pdftexnew{%
278   \pdfcrypt
279   owner{\pc@owner}%
280   user{\pc@user}%
281   \ifpc@print    \else no\fi print %
282   \ifpc@copy     \else no\fi copy %
283   \ifpc@edit     \else no\fi edit %
284   \ifpc@annotate\else no\fi annotate%
285   \relax
286 }
287 \def\pc@set@vtex{%
288   \immediate\special{!security %
289     O=\pc@MakeVTeXString\pc@owner,%
290     U=\pc@MakeVTeXString\pc@user,%
291     P\ifpc@print +\else -\fi,%
292     C\ifpc@copy +\else -\fi,%
293     M\ifpc@edit +\else -\fi,%
294     A\ifpc@annotate +\else -\fi
295   }%
296 }

```



```

297 \def\pc@MakeVTeXString#1{%
298   "\expandafter\pc@@MakeVTeXString#1"\@nil"%
299 }
300 \def\pc@@MakeVTeXString#1"#2\@nil{%
301   #1%
302   \ifx\#2\%
303   \else
304     ""%
305     \@ReturnAfterFi{%
306       \pc@MakeVTeXString#2\@nil
307     }%
308   \fi
309 }
310 \long\def\@ReturnAfterFi#1\fi{\fi#1}
311 \pc@temp
312
313 \begingroup
314   \catcode'\ =12 \gdef\pc@spaceother{ }\catcode'\ =10\relax
315   \catcode'\|=0 %
316   \catcode'\|=12 %
317   \gdef\pc@DefString#1#2{%
318     \def#1{#2}%
319     \edef#1{\expandafter\strip@prefix\meaning#1}%
320     \edef#1{\expandafter\pc@SpaceToOther#1 \@nil}%
321     \edef#1{\expandafter\pc@EscapeRemove#1|\@empty|\@empty|\@nil}%
322   }%
323   \gdef\pc@EscapeRemove#1\#2#3|\@nil{%
324     #1#2%
325     \ifx\#3|\%
326     \else
327       \@ReturnAfterFi{%
328         \pc@EscapeRemove#3|\@nil
329       }%
330     \fi
331   }%
332 \endgroup
333 \def\pc@SpaceToOther#1 #2\@nil{%
334   #1%
335   \ifx\#2\%
336   \else
337     \pc@spaceother
338     \@ReturnAfterFi{%
339       \pc@SpaceToOther#2\@nil
340     }%
341   \fi
342 }
343
344 \def\pc@boolkey{\@dblarg\pc@@boolkey}
345 \def\pc@@boolkey[#1]#2#3{%
346   \lowercase{\def\pc@temp{#3}}%
347   \ifx\pc@temp\@empty
348     \let\pc@temp\pc@true
349   \fi
350   \ifx\pc@temp\pc@true
351   \else
352     \ifx\pc@temp\pc@false
353     \else
354       \let\pc@temp\relax
355     \fi
356   \fi
357   \ifx\pc@temp\relax
358     \@PackageWarning{pdfcrypt}{%

```

```

359     Unexpected value \string'#3\string' of %
360     option \string'#2\string'\MessageBreak
361     instead of %
362     \string'true\string' or \string'false\string'%
363   }%
364 \else
365   \csname pc@#2\pc@temp\endcsname
366 \fi
367 }
368 \def\pc@true{true}
369 \def\pc@false{false}
370
371 \define@key{pc}{set}[true]{%
372   \pc@boolkey{set}{#1}%
373 }
374 \define@key{pc}{pdftex}[]{%
375   \def\pc@driver{pdftex}%
376 }
377 \define@key{pc}{vtex}[]{%
378   \def\pc@driver{vtex}%
379 }
380 \define@key{pc}{print}[true]{%
381   \pc@boolkey{print}{#1}%
382 }
383 \define@key{pc}{copy}[true]{%
384   \pc@boolkey{copy}{#1}%
385 }
386 \define@key{pc}{edit}[true]{%
387   \pc@boolkey{edit}{#1}%
388 }
389 \define@key{pc}{annotate}[true]{%
390   \pc@boolkey{annotate}{#1}%
391 }
392 \define@key{pc}{all}[]{%
393   \pc@boolkey{print}{true}%
394   \pc@boolkey{copy}{true}%
395   \pc@boolkey{edit}{true}%
396   \pc@boolkey{annotate}{true}%
397 }
398 \define@key{pc}{none}[]{%
399   \pc@boolkey{print}{false}%
400   \pc@boolkey{copy}{false}%
401   \pc@boolkey{edit}{false}%
402   \pc@boolkey{annotate}{false}%
403 }
404
405 \define@key{pc}{owner}{%
406   \pc@DefString\pc@owner{#1}%
407 }
408 \define@key{pc}{user}{%
409   \pc@DefString\pc@user{#1}%
410 }
411 \define@key{pc}{debug}[true]{%
412   \pc@boolkey{debug}{#1}%
413 }
414
415 \def\pdfcryptsetup#1{%
416   \setkeys{pc}{#1}%
417   \ifpc@set
418     \pc@set
419     \global\let\pc@set\relax
420   \gdef\pdfcryptsetup##1{%

```

```

421     \@PackageWarning{pdfcrypt}{%
422         Encryption options are already set\MessageBreak
423         new values are ignored%
424     }%
425 }%
426 \fi
427 }
428 \begingroup\expandafter\expandafter\expandafter\endgroup
429 \expandafter\ifx\csname @onlypreamble\endcsname\relax
430 \else
431     \@onlypreamble\pdfcryptsetup
432 \fi

```

## 2.6 support of configuration file

```

433 \begingroup\expandafter\expandafter\expandafter\endgroup
434 \expandafter\ifx\csname InputIfFileExists\endcsname\relax
435     \@PackageInfo{pdfcrypt}{%
436         Configuration file pdfcrypt.cfg not supported.%
437     }%
438 \else
439     \let\pc@ExecuteOptions\ExecuteOptions
440     \InputIfFileExists{pdfcrypt.cfg}{\}%
441     \let\ExecuteOptions\pc@ExecuteOptions
442 \fi

```

## 2.7 Package options

Plain format does not know package options.

```

443 \begingroup\expandafter\expandafter\expandafter\endgroup
444 \expandafter\ifx\csname @classoptionslist\endcsname\relax
445     \expandafter\pc@endinput
446 \fi

```

Process global and local options.

```

447 \def\pc@ProcessOptionsWithKV{%
448     \let\pc@temp@empty
449     \@for\CurrentOption:=\@classoptionslist\do{%
450         \@ifundefined{KV@pc@\CurrentOption}{\}%
451         \edef\pc@temp{\pc@temp,\CurrentOption,}%
452         \@expandtwoargs\@removeelement\CurrentOption
453             \@unusedeoptionlist\@unusedeoptionlist
454     }%
455 }%
456 \edef\pc@temp{%
457     \noexpand\pdfcryptsetup{%
458         \pc@temp\@optionlist{\@currname.\@current}%
459     }%
460 }%
461 \pc@temp
462 }
463 \pc@ProcessOptionsWithKV
464 \AtEndOfPackage{\let\@unprocessedoptions\relax}
465 \AtBeginDocument{\pc@set}
466
467 \pc@endinput
468 </package>

```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>2</sup>:

[CTAN:macros/latex/contrib/oberdiek/pdfcrypt.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcrypt.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for  $\TeX$  Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain  $\TeX$ :

```
tex pdfcrypt.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfcrypt.sty → tex/generic/oberdiek/pdfcrypt.sty
pdfcrypt.pdf → doc/latex/oberdiek/pdfcrypt.pdf
pdfcrypt.dtx → source/latex/oberdiek/pdfcrypt.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 3.4 Refresh file name databases

If your  $\TeX$  distribution (te $\TeX$ , mik $\TeX$ , ...) relies on file name databases, you must refresh these. For example, te $\TeX$  users run `texhash` or `mktextlsr`.

---

<sup>2</sup><ftp://ftp.ctan.org/tex-archive/>

### 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk pdfcrypt.pdf unpack_files output .
```

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for `docstrip` (really, `docstrip` does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcrypt.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex pdfcrypt.dtx
makeindex -s gind.ist pdfcrypt.idx
pdflatex pdfcrypt.dtx
makeindex -s gind.ist pdfcrypt.idx
pdflatex pdfcrypt.dtx
```

## 4 History

### [2001/04/02 v0.1]

- First public version, published in the pdftex mailing list for testing with pdfcrypt-20010331

### [2001/07/19 v0.2]

- Default: all allowed.
- Support for V<sub>T</sub>E<sub>X</sub> added.

### [2001/07/19 v0.3]

- Bug fix: V<sub>T</sub>E<sub>X</sub> letter for edit is M (modify).

### [2001/07/19 v0.4]

- Bug fix: `\VTexversion` is correct after regenerating the format file.

### [2001/08/05 v0.5]

- Syntax change in pdfT<sub>E</sub>X 1.00a.

## [2001/08/09 v0.6]

- Support of special characters:  
input: `\{, \}, \\` for `{, }, \`  
output: " in `VTEX`
- Option `debug` added.

## [2001/10/28 v0.7]

- Plain compatibility.
- `\nopdfcrypt` added.
- Typos corrected.

## [2006/02/20 v0.8]

- Obsolete remarks for `pdfTEX`.
- DTX framework.
- LPPL 1.3

## [2007/04/11 v0.9]

- Line ends sanitized.

## [2007/04/26 v1.0]

- Use of package `infwarerr`.

# 5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\"</code> .....	215, 216
<code>\#</code> .....	323, 325
<code>\%</code> .....	325
<code>\:</code> .....	46, 47, 48, 49
<code>\@</code> .....	3, 6
<code>\@PackageError</code> .....	100, 118, 249, 252
<code>\@PackageInfo</code> .....	218, 435
<code>\@PackageWarning</code> .....	358, 421
<code>\@PackageWarningNoLine</code> .....	82, 87
<code>\@ReturnAfterFi</code> .....	305, 310, 338
<code>\@classoptionslist</code> .....	449
<code>\@currrent</code> .....	458
<code>\@currname</code> .....	458
<code>\@dblarg</code> .....	196, 344
<code>\@ehc</code> .....	250, 253
<code>\@empty</code> .....	75, 92, 206, 207, 220, 226, 248, 347, 448
<code>\@expandtwoargs</code> .....	452
<code>\@firstoftwo</code> .....	9, 19
<code>\@for</code> .....	449
<code>\@gobble</code> .....	71, 80
<code>\@ifnch</code> .....	31, 33, 49
<code>\@ifnextchar</code> .....	27, 55, 196
<code>\@ifundefined</code> .....	17, 26, 53, 70, 74, 79, 95, 99, 114, 117, 131, 135, 144, 148, 157, 165, 173, 181, 195, 247, 450
<code>\@let@token</code> .....	31, 34, 37, 49
<code>\@makeother</code> .....	132, 216
<code>\@namedef</code> .....	145
<code>\@nameuse</code> .....	149, 256
<code>\@nil</code> .....	298, 300, 306, 333, 339
<code>\@onlypreamble</code> .....	431
<code>\@optionlist</code> .....	458
<code>\@removeelement</code> .....	452
<code>\@secondoftwo</code> .....	13, 21
<code>\@sptoken</code> .....	34, 46
<code>\@undefined</code> .....	153
<code>\@unprocessedoptions</code> .....	464
<code>\@unusedoptionlist</code> .....	453
<code>\@xdblarg</code> .....	196, 197
<code>\@xifnch</code> .....	35, 48
<code>\\</code> .....	302, 316, 335
<code>\ </code> .....	315, 321

<code>\l</code> .....	314	<code>\pc@annotatetrue</code> .....	213
<b>A</b>		<code>\pc@boolkey</code> .....	344, 372, 381, 384, 387, 390, 393, 394, 395, 396, 399, 400, 401, 402, 412
<code>\AtBeginDocument</code> .....	465	<code>\pc@copytrue</code> .....	211
<code>\AtEndOfPackage</code> .....	464	<code>\pc@DefString</code> .....	406, 409
<b>C</b>		<code>\pc@driver</code> .....	92, 109, 126, 242, 247, 248, 253, 256, 375, 378
<code>\catcode</code> ..	3, 6, 132, 215, 314, 315, 316	<code>\pc@edittrue</code> .....	212
<code>\csname</code> .....	2, 8, 12, 16, 18, 64, 145, 149, 189, 365, 429, 434, 444	<code>\pc@endinput</code> ...	83, 107, 124, 445, 467
<code>\CurrentOption</code> .....	449, 450, 451, 452	<code>\pc@ExecuteOptions</code> .....	439, 441
<b>D</b>		<code>\pc@false</code> .....	352, 369
<code>\DeclareOption</code> .....	164, 166, 168	<code>\pc@KeyvalRestore</code> .....	. 152, 153, 159, 167, 175, 183, 194
<code>\define@key</code>	371, 374, 377, 380, 383, 386, 389, 392, 398, 405, 408, 411	<code>\pc@MakeVTeXString</code> ...	289, 290, 297
<code>\do</code> .....	449	<code>\pc@nopdfcrypttrue</code> .....	90
<b>E</b>		<code>\pc@owner</code> .....	. 206, 220, 223, 269, 279, 289, 406
<code>\endcsname</code> .....	2, 8, 12, 16, 18, 64, 145, 149, 189, 365, 429, 434, 444	<code>\pc@printtrue</code> .....	210
<code>\endinput</code> .....	4	<code>\pc@ProcessOptionsWithKV</code> ...	447, 463
<code>\ExecuteOptions</code>	172, 174, 176, 439, 441	<code>\pc@ProvidesPackage</code> .....	55, 56, 58
<b>F</b>		<code>\pc@set</code> .....	217, 418, 419, 465
<code>\futurelet</code> .....	31, 49	<code>\pc@set@pdftex</code> .....	260
<b>G</b>		<code>\pc@set@pdftexnew</code> .....	264, 277
<code>\g@addto@macro</code>	136, 159, 167, 175, 183	<code>\pc@set@pdftexold</code> .....	262, 267
<code>\gdef</code> .....	49, 109, 126, 314, 420	<code>\pc@set@vtex</code> .....	287
<b>I</b>		<code>\pc@spaceother</code> .....	314, 337
<code>\ifcase</code> .....	97	<code>\pc@SpaceToOther</code> .....	333, 339
<code>\ifnum</code> .....	116, 117, 261	<code>\pc@temp</code> .....	215, 311, 346, 347, 348, 350, 352, 354, 357, 365, 448, 451, 456, 458, 461
<code>\ifpc@annotate</code>	204, 236, 274, 284, 294	<code>\pc@true</code> .....	348, 350, 368
<code>\ifpc@copy</code> ...	202, 234, 272, 282, 292	<code>\pc@user</code>	207, 226, 229, 270, 280, 290, 409
<code>\ifpc@debug</code> .....	205, 219	<code>\pc@Org@DeclareOption</code> .....	164, 168
<code>\ifpc@edit</code> ...	203, 235, 273, 283, 293	<code>\pc@Org@ExecuteOptions</code> .....	172, 176
<code>\ifpc@nopdfcrypt</code> .....	85, 239, 245	<code>\pc@Org@NeedsTeXFormat</code> .....	156, 160
<code>\ifpc@print</code> ...	201, 233, 271, 281, 291	<code>\pc@Org@ProcessOptions</code> .....	180, 184
<code>\ifpc@set</code> .....	200, 417	<code>\pdfcrypt</code> .....	268, 278
<code>\ifx</code> .....	8, 12, 16, 18, 34, 37, 64, 86, 189, 220, 226, 248, 302, 335, 347, 350, 352, 357, 429, 434, 444	<code>\pdfcryptsetup</code> .	80, 415, 420, 431, 457
<code>\immediate</code> .....	59, 288	<code>\pdfoutput</code> .....	97
<code>\input</code> .....	65, 190	<code>\pdftexversion</code> .....	261
<code>\InputIfFileExists</code> .....	440	<code>\ProcessOptions</code> .....	180, 182, 184
<b>L</b>		<code>\ProvidesPackage</code> .....	54, 77
<code>\lowercase</code> .....	346	<b>R</b>	
<b>M</b>		<code>\RequirePackage</code> .....	67, 192
<code>\MessageBreak</code> .....	..... 103, 225, 231, 237, 360, 422	<code>\reserved@a</code> .....	29, 38
<b>N</b>		<code>\reserved@b</code> .....	30, 40
<code>\NeedsTeXFormat</code> .....	156, 158, 160	<code>\reserved@c</code> .....	35, 38, 40, 43
<code>\newif</code> .	85, 200, 201, 202, 203, 204, 205	<code>\reserved@d</code> .....	28, 37
<code>\nopdfcrypt</code> .....	86, 88, 240	<b>S</b>	
<b>O</b>		<code>\setkeys</code> .....	416
<code>\OpMode</code> .....	116	<code>\space</code> .....	88
<b>P</b>		<code>\special</code> .....	288
<code>\pc@boolkey</code> .....	344, 345	<b>T</b>	
<code>\pc@MakeVTeXString</code> ...	298, 300, 306	<code>\the</code> .....	3, 139, 215
<b>V</b>		<code>\toks@</code> .....	138, 139
<code>\VTeXversion</code> .....	117	<b>W</b>	
<b>W</b>		<code>\write</code> .....	59