

1. Function and Use.

This small program will convert Big 5 encoded Chinese characters into a ‘preprocessed’ form. The need of this program arises from the fact that this encoding uses the characters ‘\’, ‘{’, and ‘}’ which have special meanings in \TeX .

Use this program as a filter:

```
bg5conv < input_file > output_file
```

2. The program.

The only function of this program is to replace all occurrences of Big 5 encoded characters XY (X and Y are the first and the second byte of the character) with $\text{\textasciix}^{\text{ZZZ}}$, where ZZZ represents the second byte as a decimal number. $0x7F$ is used as an active character and delimiter.

Additionally we define a \TeX macro at the very beginning to signal a preprocessed file.

The following code is very simple. No error detection is done because \TeX which will see the output of `bg5conv` complains loudly if something is wrong.

```
#define banner "bg5conv\_(CJK\_(ver.\_4.8.2))"
#include <stdio.h>
#include <stdlib.h>

int main(argc, argv)
    int argc;
    char *argv[];
{int ch;
  fprintf(stdout, "\\def\\CJKpreproc{%s}", banner);
  ch = fgetc(stdin);
  while (!feof(stdin))
  {if (ch >= #A1 & ch <= #FE)
    {fprintf(stdout, "\\177%c\177", ch);
     ch = fgetc(stdin);
     if (!feof(stdin))
       fprintf(stdout, "%d\177", ch);
    }
    else
      fputc(ch, stdout);
    ch = fgetc(stdin);
  }
  exit(EXIT_SUCCESS);
return 0;
}
```

/* never reached */